



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
[www.uspto.gov](http://www.uspto.gov)

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/334,424	06/16/1999	YASUTOMO NISHINA	450100-4916	5326
20999 7590 08/13/2008 FROMMER LAWRENCE & HAUG 745 FIFTH AVENUE- 10TH FL. NEW YORK, NY 10151				
EXAMINER				
SALCE, JASON P				
ART UNIT		PAPER NUMBER		
2623				
MAIL DATE		DELIVERY MODE		
08/13/2008		PAPER		

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

# Office Action Summary

**Application No.**

09/334,424

**Applicant(s)**

NISHINA ET AL.

**Examiner**

Jason P. Salce

**Art Unit**

2623

**Period for Reply** -- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 29 February 2008.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 44-68 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 44-68 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
- Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
- Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some \* c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
  - ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- 1) ☐ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☒ Information Disclosure Statement(s) (PTO/SB/08)
- Paper No(s)/Mail Date: 7/2/2007
- 4) ☐ Interview Summary (PTO-413)
- Paper No(s)/Mail Date: \_\_\_\_\_
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: \_\_\_\_\_

## DETAILED ACTION

### ***Continued Examination Under 37 CFR 1.114***

A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 10/31/2007 has been entered.

All claims are drawn to the same invention claimed in the application prior to the entry of the submission under 37 CFR 1.114 and could have been finally rejected on the grounds and art of record in the next Office action if they had been entered in the application prior to entry under 37 CFR 1.114. Although Applicant has stated that new claims 44-68 are similar to 1-15, 17, 19 and 21-28, they are identical.

Accordingly, **THIS ACTION IS MADE FINAL** even though it is a first action after the filing of a request for continued examination and the submission under 37 CFR 1.114. See MPEP § 706.07(b). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any

extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

### ***Response to Arguments***

Applicant argues that Matsuzaki fails to teach controlling said multiplexing ratio to enable acquisition of program information in a reduced period of time by increasing transmission of program data when transmission of video data and audio data can be decreased.

The examiner disagrees and notes that the previously cited passages clearly teach a priority for multiplexing and transmitting data to a client, which therefore clearly teaches controlling a multiplexing ratio by only sending specific data to a client and discarding others. Further these passages teach enabling acquisition of program information in a reduced period of time by increasing transmission of program data when transmission of video data and audio data can be decreased, by teaching preferential multiplexing of specific types of data over further types of data, therefore if data type A is preferred, the system multiplexes data type A over data types B and C, therefore increasing the transmission of data type A and decreasing the transmission of data types B and C (further note Column 5, Line 14 through Column 6, Line 39 for further support of using the priority process for multiplexing and transmission of specific media data types).

***Claim Rejections - 35 USC § 103***

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Claims 44-52 and 62-64 are rejected under 35 U.S.C. 103(a) as being unpatentable over Matsuzaki et al. (U.S. Patent No. 6,522,672) in view of Shiroshita et al. (U.S. Patent No. 5,892,894).

Referring to claim 44, Matsuzaki discloses an information transmitting apparatus, which transmits a plurality of signals (see Figure 1), said signals including at least video signals and audio signals (see Column 4, Lines 45-48), to an information receiving apparatus (see Column 9, Lines 24-25 for receiving information at a receiver).

Matsuzaki also discloses a plurality of encoding means for separately encoding each of said video signals and each of said audio signals (see elements 82v and 82a in Figure 2).

Matsuzaki also discloses a first multiplexing means for multiplexing a plurality of pairs of encoded signals (see elements 34a through 34n in Figure 3), each pair of encoded signals having one encoded video signal and one encoded audio signal (see Column 4, Lines 41-50).

Matsuzaki also discloses a second multiplexing means for multiplexing the multiplexed plurality of pairs of encoded video signals and encoded audio signals (see Column 5, Lines 66-67 and Column 6, Lines 1-4).

Matsuzaki also discloses a control means for controlling a multiplexing ratio among the plurality of signals in the second multiplexing means (see Column 5, Lines 38-45 and Column 6, Lines 5-9 for the second multiplexing means being controlled by the control means).

Matsuzaki discloses at Column 4, Lines 45-49 that multiplexing section 34 multiplexes a plurality of media encoded bit streams 75 for each packet (which can include video, audio and data). Matsuzaki further discloses that the multiplexing control indicates preferentially multiplexing of the information with higher priority by controlling on/off of the multiplexing according to the priority for each encoded bit stream 75 (see Column 4, Lines 63-67). For further support, note Column 6, Line 60 through Column 7, Line 16 for multiplexing according to a priority table. Therefore, a video, audio and data occupation bandwidth is clearly controlled.

**Matsuzaki further teaches that said control means controls said multiplexing ratio to enable acquisition of program information in a reduced period of time by increasing transmission of program data when transmission of video data and audio data can be decreased (see Column 2, Lines 26-28, 35-39 and 65-66 and Column 3, Lines 1-4 and Column 4, Line 63 through Column 5, Line 3 for controlling the multiplexing ratio by controlling how much information is added to the encoded bit stream, which in turn “that multiplexing or not multiplexing certain media information is supposed to control a transmission rate of the media information”).** Therefore, if audio and video data have a low priority

**and program information has a high priority, more program information will be transmitted, thereby increasing the transmission rate of the program.**

Matsuzaki teaches that the information receiving apparatus reads contents of program information of a current and a next program (see Column 9, Lines 23-25), but not at a re-transmission cycle of the program information data. Matsuzaki also teaches recognizing a transmission status of the program information data indicating broadcast schedules (see Column 5, Lines 31-45 for multiplexing the program information data according to information which specifies optimal transmission of the media, therefore recognizing a transmission status required for proper transmission of the media to the receiving apparatus).

Shiroshita discloses a data re-transmission process that detects if a terminal is providing poor performance in the network and retransmits packets at a cycle representative of the terminal's performance state (see Column 4, Line 59 through Column 5, Line 30).

At the time the invention was made, it would have been obvious to a person of ordinary skill in the art, to modify the transmission system, as taught by Matsuzaki, using the re-transmission system, as taught by Shiroshita, for the purpose of improving the communication efficiency (see Column 2, Lines 60-61 of Shiroshita).

Referring to claim 45, Matsuzaki discloses that the transmitting apparatus transmits the plurality of signals as a single transport stream (see Column 8, Lines 40-44 for transmitting a single transport stream).

Referring to claim 46, Matsuzaki discloses a database means for providing data that relates to transmission rates of the plurality of signals at each time point (see Figure 4 for a priority correlation table for indicating priorities for multiple types of media and Column 7, Lines 20-22 and Column 5, Lines 46-53 for adding time information so that a "time point" can therefore be determined), wherein the control means controls the multiplexing ratio while referring to the database (see Column 8, Lines 1-7).

Referring to claim 47, Matsuzaki discloses that the control means controls an output rate each of the plurality of the encoding means (see again Column 8, Lines 1-7 and note that setting the multiplexer with a priority for either the video, audio or data will control the output rate of that particular piece of information).

Referring to claim 48, Matsuzaki discloses that the pluralities of signals further comprise program information (see Column 4, Lines 45-48).

Referring to claim 49, that Matsuzaki discloses an information transmitting apparatus, which transmits program information (see Figure 1), to an information receiving apparatus (see Column 9, Lines 24-25 for receiving information at a receiver).

Matsuzaki also discloses a plurality of video and audio encoding means (see elements 82a, 82v in Figure 2).



Matsuzaki also discloses a program information data generating means for generating data of the program information (see elements 82d in Figure 1).

Matsuzaki also discloses a first multiplexing means for multiplexing the program information, video and audio (see element 34 in Figure 1 and Column 4, Lines 41-50 for forming pairs of the multiplexed data).

Matsuzaki also discloses a control means for controlling a data output rate of the video, audio and program information by controlling a multiplexing ratio between these data elements (see Column 5, Lines 38-45 and Column 6, Lines 5-9 for the second multiplexing means being controlled by the control means).

Matsuzaki discloses at Column 4, Lines 45-49 that multiplexing section 34 multiplexes a plurality of media encoded bit streams 75 for each packet (which can include video, audio and data). Matsuzaki further discloses that the multiplexing control indicates preferentially multiplexing of the information with higher priority by controlling on/off of the multiplexing according to the priority for each encoded bit stream 75 (see Column 4, Lines 63-67). For further support, note Column 6, Line 60 through Column 7, Line 16 for multiplexing according to a priority table. Therefore, a video, audio and data occupation bandwidth is clearly controlled.

**Matsuzaki further teaches that said control means controls said multiplexing ratio to enable acquisition of program information in a reduced period of time by increasing transmission of program data when transmission of video data and audio data can be decreased (see Column 2, Lines 26-28, 35-39 and 65-66 and Column 3, Lines 1-4 and Column 4, Line 63 through Column 5, Line**

**3 for controlling the multiplexing ratio by controlling how much information is added to the encoded bit stream, which in turn “that multiplexing or not multiplexing certain media information is supposed to control a transmission rate of the media information”).** Therefore, if audio and video data have a low priority and program information has a high priority, more program information will be transmitted, thereby increasing the transmission rate of the program.

Matsuzaki teaches that the information receiving apparatus reads contents of program information of a current and a next program (see Column 9, Lines 23-25), but not at a re-transmission cycle of the program information data. Matsuzaki also teaches recognizing a transmission status of the program information data indicating broadcast schedules (see Column 5, Lines 31-45 for multiplexing the program information data according to information which specifies optimal transmission of the media, therefore recognizing a transmission status required for proper transmission of the media to the receiving apparatus).

Shiroshita discloses a data re-transmission process that detects if a terminal is providing poor performance in the network and retransmits packets at a cycle representative of the terminal's performance state (see Column 4, Line 59 through Column 5, Line 30).

At the time the invention was made, it would have been obvious to a person of ordinary skill in the art, to modify the transmission system, as taught by Matsuzaki, using the re-transmission system, as taught by Shiroshita, for the purpose of improving the communication efficiency (see Column 2, Lines 60-61 of Shiroshita).

Referring to claims 50-52, see rejection of claims 44, 46 and 48, respectively.

Referring to claims 62-64, see the rejection of claim 44.

Claims 53-57 are rejected under 35 U.S.C. 103(a) as being unpatentable over Matsuzaki et al. (U.S. Patent No. 6,522,672) in view of Shiroshita et al. (U.S. Patent No. 5,892,894) in further view of Eyer et al. (U.S. Patent No. 5,801,753).

Referring to claim 53, that Matsuzaki discloses an information transmitting apparatus, which transmits program information (see Figure 1), to an information receiving apparatus (see Column 9, Lines 24-25 for receiving information at a receiver).

Matsuzaki also discloses a plurality of video and audio encoding means (see elements 82a, 82v in Figure 2).

Matsuzaki also discloses a program information data generating means for generating data of the program information (see elements 82d in Figure 1).

Matsuzaki also discloses a first multiplexing means for multiplexing the program information, video and audio (see element 34 in Figure 1 and Column 4, Lines 41-50 for forming pairs of the multiplexed data).

Matsuzaki also discloses a control means for controlling a data output rate of the video, audio and program information by controlling a multiplexing ratio between these data elements (see Column 5, Lines 38-45 and Column 6, Lines 5-9 for the second multiplexing means being controlled by the control means).

Matsuzaki discloses at Column 4, Lines 45-49 that multiplexing section 34 multiplexes a plurality of media encoded bit streams 75 for each packet (which can include video, audio and data). Matsuzaki further discloses that the multiplexing control indicates preferentially multiplexing of the information with higher priority by controlling on/off of the multiplexing according to the priority for each encoded bit stream 75 (see Column 4, Lines 63-67). For further support, note Column 6, Line 60 through Column 7, Line 16 for multiplexing according to a priority table. Therefore, a video, audio and data occupation bandwidth is clearly controlled.

**Matsuzaki further teaches that said control means controls said multiplexing ratio to enable acquisition of program information in a reduced period of time by increasing transmission of program data when transmission of video data and audio data can be decreased (see Column 2, Lines 26-28, 35-39 and 65-66 and Column 3, Lines 1-4 and Column 4, Line 63 through Column 5, Line 3 for controlling the multiplexing ratio by controlling how much information is added to the encoded bit stream, which in turn “that multiplexing or not multiplexing certain media information is supposed to control a transmission rate of the media information”). Therefore, if audio and video data have a low priority and program information has a high priority, more program information will be transmitted, thereby increasing the transmission rate of the program.**

Matsuzaki teaches that the information receiving apparatus reads contents of program information of a current and a next program (see Column 9, Lines 23-25), but not at a re-transmission cycle of the program information data. Matsuzaki also teaches

recognizing a transmission status of the program information data indicating broadcast schedules (see Column 5, Lines 31-45 for multiplexing the program information data according to information which specifies optimal transmission of the media, therefore recognizing a transmission status required for proper transmission of the media to the receiving apparatus).

Shiroshita discloses a data re-transmission process that detects if a terminal is providing poor performance in the network and retransmits packets at a cycle representative of the terminal's performance state (see Column 4, Line 59 through Column 5, Line 30).

At the time the invention was made, it would have been obvious to a person of ordinary skill in the art, to modify the transmission system, as taught by Matsuzaki, using the re-transmission system, as taught by Shiroshita, for the purpose of improving the communication efficiency (see Column 2, Lines 60-61 of Shiroshita).

Matsuzaki and Shiroshita fail to disclose that the information receiving apparatus is adapted to acquire electronic program guide data only during a data transfer rate increase period.

Eyer teaches a separating and storing program information (trickle data streams and demand data streams of EPG data) according to selections made by the user (if EPG data stored in local memory (trickle data) is selected or EPG data that has to be transmitted to a user (demand data)) at Column 12, Lines 55-67 and Column 13, Lines 1-10 for receiving both types of data at different transmission rates and separating and

storing the data accordingly. Also note Column 6, Lines 5-8 for selecting a specific type of EPG data and Column 3, Lines 35-55 for storing EPG data at different rates.

Eyer therefore teaches acquiring electronic program guide data only during a data transfer rate increase period (also see Column 3, Lines 47-51 and Column 5, Lines 62-67 and Column 6, Lines 1-8).

At the time the invention was made, it would have been obvious to a person of ordinary skill in the art, to modify the information receiving apparatus, as taught by Matsuzaki and Shiroshita, using the trickle and demand EPG data transmission rate functionality, as taught by Eyer, for the purpose of improving the responsiveness and user friendliness of the program guide function by ensuring that the memory in a subscriber's decoder always holds a database which is up-to-date for current programming (see Column 5, Lines 64-67 and Column 6, Line 1 of Eyer).

Referring to claim 54, see the rejection of claim 10.

Referring to claim 55, Matsuzaki discloses a database means for providing data that relates to transmission rates of the plurality of signals at each time point (see Figure 4 for a priority correlation table for indicating priorities for multiple types of media and Column 7, Lines 20-22 and Column 5, Lines 46-53 for adding time information so that a "time point" can therefore be determined), wherein the control means controls the multiplexing ratio while referring to the database (see Column 8, Lines 1-7).

Referring to claim 56, Matsuzaki discloses that the pluralities of signals further comprise program information (see Column 4, Lines 45-48).

Referring to claim 57, see the rejection of claim 53.

Claims 58, 59, 60, 61 and 65-68 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ozkan et al. (U.S. Patent No. 6,111,612) in view of Eyer et al. (U.S. Patent No. 5,801,753) in further view of Matsuzaki et al. (U.S. Patent No. 6,522,672) in further view of Shiroshita et al. (U.S. Patent No. 5,892,894).

Referring to claim 58, Ozkan discloses an information receiving apparatus (see Figure 1), which receives multiplexed program information (see element 22 in Figure 1 and Column 3, Lines 19-20 for demultiplexing a multiplexed program information signal).

Ozkan also discloses separating means for separating the multiplexed program information (see again Column 3, Lines 19-20 for a demultiplexer used for separating the video, audio and data).

Ozkan also discloses a plurality of decoding means for separately decoding each of the video signals and each of the audio signals (see Column 3, Lines 20-24 for a plurality of decoders used for decoding the separated audio and video).

Ozkan also discloses a storing means for storing the program information separated by the separating means (see Column 3, Lines 53-56).

Ozkan also discloses a control means for controlling operations of the separating means and the storing means (see Column 4, Lines 17-19 for controlling the storing operation from demultiplexer 22 by processor 60 and Column 3, Lines 30-33 for separating a channel for viewing using the processor 60).

Ozkan is silent as to storing and separating program information in accordance with a transmission rate of the program information.

Eyer teaches a separating and storing program information (trickle data streams and demand data streams of EPG data) according to selections made by the user (if EPG data stored in local memory (trickle data) is selected or EPG data that has to be transmitted to a user (demand data)) at Column 12, Lines 55-67 and Column 13, Lines 1-10 for receiving both types of data at different transmission rates and separating and storing the data accordingly. Also note Column 6, Lines 5-8 for selecting a specific type of EPG data and Column 3, Lines 35-55 for storing EPG data at different rates.

Eyer therefore teaches acquiring electronic program guide data only during a data transfer rate increase period (also see Column 3, Lines 47-51 and Column 5, Lines 62-67 and Column 6, Lines 1-8).

Eyer also teaches the use of time slots (see Column 7, Lines 1-8) and that packets are filtered according to the page and time slot of interest (see Column 7, Lines 9-26), therefore controlling a data acquisition time of the program information. Also note Column 2, Lines 28-39 for further support.

At the time the invention was made, it would have been obvious to a person of ordinary skill in the art, to modify the information receiving apparatus, as taught by



Ozkan, using the trickle and demand EPG data transmission rate functionality, as taught by Eyer, for the purpose of improving the responsiveness and user friendliness of the program guide function by ensuring that the memory in a subscriber's decoder always holds a database which is up-to-date for current programming (see Column 5, Lines 64-67 and Column 6, Line 1 of Eyer).

Although Ozkan and Eyer disclose receiving a plurality of signals multiplexed together, Ozkan and Eyer are silent as to the program information being comprised of multiplexed pairs of encoded signals, each pair of encoded signals having one encoded video signal and one encoded audio signals.

Matsuzaki teaches a first multiplexing means for multiplexing a plurality of pairs of encoded signals (see elements 34a through 34n in Figure 3), each pair of encoded signals having one encoded video signal and one encoded audio signal (see Column 4, Lines 41-50).

**Matsuzaki further teaches that said control means controls said multiplexing ratio to enable acquisition of program information in a reduced period of time by increasing transmission of program data when transmission of video data and audio data can be decreased (see Column 2, Lines 26-28, 35-39 and 65-66 and Column 3, Lines 1-4 and Column 4, Line 63 through Column 5, Line 3 for controlling the multiplexing ratio by controlling how much information is added to the encoded bit stream, which in turn “that multiplexing or not multiplexing certain media information is supposed to control a transmission rate of the media information”).** Therefore, if audio and video data have a low priority

**and program information has a high priority, more program information will be transmitted, thereby increasing the transmission rate of the program.**

At the time the invention was made, it would have been obvious to a person of ordinary skill in the art, to modify the information receiving apparatus, as taught by Ozkan and Eyer, using the multiplexed pairs of audio and video signals, as taught by Matsuzaki, for the purpose of allowing a receiver to easily edit or process the information (see Column 9, Lines 22-24 of Matsuzaki).

Matsuzaki teaches that the information receiving apparatus reads contents of program information of a current and a next program (see Column 9, Lines 23-25), however, Matsuzaki, Eyer and Ozkan fail to teach this process at a re-transmission cycle of the program information data.

Matsuzaki also teaches recognizing a transmission status of the program information data indicating broadcast schedules (see Column 5, Lines 31-45 for multiplexing the program information data according to information which specifies optimal transmission of the media, therefore recognizing a transmission status required for proper transmission of the media to the receiving apparatus).

Shiroshita discloses a data re-transmission process that detects if a terminal is providing poor performance in the network and retransmits packets at a cycle representative of the terminal's performance state (see Column 4, Line 59 through Column 5, Line 30).

At the time the invention was made, it would have been obvious to a person of ordinary skill in the art, to modify the transmission system, as taught by Ozkan, Eyer

and Matsuzaki, using the re-transmission system, as taught by Shiroshita, for the purpose of improving the communication efficiency (see Column 2, Lines 60-61 of Shiroshita).

Referring to claim 59, see the rejection of claim 58.

Referring to claim 60, see the rejection of claims 58.

Referring to claim 61, Ozkan discloses an information receiving apparatus (see Figure 1), which receives multiplexed program information (see element 22 in Figure 1 and Column 3, Lines 19-20 for demultiplexing a multiplexed program information signal).

Ozkan also discloses separating means for separating the multiplexed program information (see again Column 3, Lines 19-20 for a demultiplexer used for separating the video, audio and data).

Ozkan also discloses a plurality of decoding means for separately decoding each of the video signals and each of the audio signals (see Column 3, Lines 20-24 for a plurality of decoders used for decoding the separated audio and video).

Ozkan also discloses a storing means for storing the program information separated by the separating means (see Column 3, Lines 53-56).

Ozkan also discloses a control means for controlling operations of the separating means and the storing means (see Column 4, Lines 17-19 for controlling the storing

operation from demultiplexer 22 by processor 60 and Column 3, Lines 30-33 for separating a channel for viewing using the processor 60).

Ozkan is silent as to storing and separating program information in accordance with a transmission rate of the program information.

Eyer teaches a separating and storing program information (trickle data streams and demand data streams of EPG data) according to selections made by the user (if EPG data stored in local memory (trickle data) is selected or EPG data that has to be transmitted to a user (demand data)) at Column 12, Lines 55-67 and Column 13, Lines 1-10 for receiving both types of data at different transmission rates and separating and storing the data accordingly. Also note Column 6, Lines 5-8 for selecting a specific type of EPG data and Column 3, Lines 35-55 for storing EPG data at different rates.

Eyer therefore teaches acquiring electronic program guide data only during a data transfer rate increase period (also see Column 3, Lines 47-51 and Column 5, Lines 62-67 and Column 6, Lines 1-8).

Eyer teaches the use of time slots (see Column 7, Lines 1-8) and that packets are filtered according to the page and time slot of interest (see Column 7, Lines 9-26), therefore controlling a data acquisition time of the program information. Also note Column 2, Lines 28-39 for further support.

At the time the invention was made, it would have been obvious to a person of ordinary skill in the art, to modify the information receiving apparatus, as taught by Ozkan, using the trickle and demand EPG data transmission rate functionality, as taught by Eyer, for the purpose of improving the responsiveness and user friendliness of the

program guide function by ensuring that the memory in a subscriber's decoder always holds a database which is up-to-date for current programming (see Column 5, Lines 64-67 and Column 6, Line 1 of Eyer).

Although Ozkan and Eyer disclose receiving a plurality of signals multiplexed together, Ozkan and Eyer are silent as to the program information being comprised of multiplexed pairs of encoded signals, each pair of encoded signals having one encoded video signal and one encoded audio signals and are also silent as to the details of the transmitting apparatus.

Matsuzaki discloses an information transmitting apparatus, which transmits a plurality of signals (see Figure 1), said signals including at least video signals and audio signals (see Column 4, Lines 45-48), to an information receiving apparatus (see Column 9, Lines 24-25 for receiving information at a receiver).

Matsuzaki also discloses a plurality of encoding means for separately encoding each of said video signals and each of said audio signals (see elements 82v and 82a in Figure 2).

Matsuzaki also discloses a first multiplexing means for multiplexing a plurality of pairs of encoded signals (see elements 34a through 34n in Figure 3), each pair of encoded signals having one encoded video signal and one encoded audio signal (see Column 4, Lines 41-50).

Matsuzaki also discloses a second multiplexing means for multiplexing the multiplexed plurality of pairs of encoded video signals and encoded audio signals (see Column 5, Lines 66-67 and Column 6, Lines 1-4).

Matsuzaki also discloses a control means for controlling a multiplexing ratio among the plurality of signals in the second multiplexing means (see Column 5, Lines 38-45 and Column 6, Lines 5-9 for the second multiplexing means being controlled by the control means).

**Matsuzaki further teaches that said control means controls said multiplexing ratio to enable acquisition of program information in a reduced period of time by increasing transmission of program data when transmission of video data and audio data can be decreased (see Column 2, Lines 26-28, 35-39 and 65-66 and Column 3, Lines 1-4 and Column 4, Line 63 through Column 5, Line 3 for controlling the multiplexing ratio by controlling how much information is added to the encoded bit stream, which in turn “that multiplexing or not multiplexing certain media information is supposed to control a transmission rate of the media information”). Therefore, if audio and video data have a low priority and program information has a high priority, more program information will be transmitted, thereby increasing the transmission rate of the program.**

At the time the invention was made, it would have been obvious to a person of ordinary skill in the art, to modify the information receiving system, as taught by Ozkan and Eyer, using the transmitting apparatus, as taught by Matsuzaki, for the purpose of allowing a receiver to easily edit or process the information (see Column 9, Lines 22-24 of Matsuzaki).

Matsuzaki teaches that the information receiving apparatus reads contents of program information of a current and a next program (see Column 9, Lines 23-25),

however, Ozkan, Eyer and Matsuzaki fail to teach this process at a re-transmission cycle of the program information data. Matsuzaki also teaches recognizing a transmission status of the program information data indicating broadcast schedules (see Column 5, Lines 31-45 for multiplexing the program information data according to information which specifies optimal transmission of the media, therefore recognizing a transmission status required for proper transmission of the media to the receiving apparatus).

Shiroshita discloses a data re-transmission process that detects if a terminal is providing poor performance in the network and retransmits packets at a cycle representative of the terminal's performance state (see Column 4, Line 59 through Column 5, Line 30).

At the time the invention was made, it would have been obvious to a person of ordinary skill in the art, to modify the transmission system, as taught by Ozkan, Eyer and Matsuzaki, using the re-transmission system, as taught by Shiroshita, for the purpose of improving the communication efficiency (see Column 2, Lines 60-61 of Shiroshita).

Referring to claims 65-67, see the rejection of claim 58, and note that Eyer discloses extracting information of a transmission status of the program information that is included in the program information data separated by the separating means (see Column 11, Lines 10-23 for extracting a field of the program information that states if the status of the transmission is trickle data or demand data).

Referring to claim 68, see the rejection of claim 61 and note that Eyer discloses extracting information of a transmission status of the program information that is included in the program information data separated by the separating means (see Column 11, Lines 10-23 for extracting a field of the program information that states if the status of the transmission is trickle data or demand data).

### ***Conclusion***

**THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Jason P. Salce whose telephone number is (571) 272-7301. The examiner can normally be reached on M-F 9am-6pm.



If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, John Miller can be reached on (571) 272-7353. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Jason P Salce/  
Primary Examiner, Art Unit 2623

Jason P Salce  
Primary Examiner  
Art Unit 2623

August 11, 2008